




SPECIFICATION DATA



Parameters		Type	
		KPWR	KPWS
Flow Rate,	lpm [GPM]	60	[15.85]
Pressure Range*,	bar [PSI]	250	[3625]
Weight,	kg	0,850	0,670
	[lb]	[1.874]	[1.477]



VALVE for MP, MR, MH HYDRAULIC MOTORS
KPWR



VALVE for MS HYDRAULIC MOTORS
KPWS



	Thread Ports - P _(A,B)	Thread Ports - C
-	G1/2 17 [.67] depth	G1/4 14 [.55] depth
M	M22x1,5 17 [.67] depth	M14x1,5 14 [.55] depth
A	7/8 - 14 UNF O-ring 17 [.67] depth	7/16 - 20 UNF O-ring 12,7 [.50] depth

Note: KPWR Blocks are installed directly on MP, MR and MH Motors with four screws M8x30 - 8.8 DIN 912 or 5/16-18UNC, 1.25 [.049] long ANSI B 18.3 .

Tightening torque 2,0^{+0,5} daNm [177⁺⁴⁴ lb-in].


KPWS Blocks are installed directly on MS Motors with two screws M10x35 - 8.8 DIN 912 or 3/8-16UNC, 1.5 [.059] long ANSI B 18.3. Tightening torque 3,5 daNm [336 lb-in].

SWITCH VALVE (continued)


SPECIFICATION DATA

Parameters		Type	
		KPWT	KPWV
Flow Rate,	lpm [GPM]	100 [26.4]	2100 [52.8]
Pressure Range,	bar [PSI]	250	[3625]
Weight,	kg	1,800	3,150
	[lb]	[3.968]	[6.945]

VALVE for MT HYDRAULIC MOTORS KPWT



VALVE for MV HYDRAULIC MOTORS KPWV



	Thread Ports - P _(A,B)	Thread Ports - C
-	G3/4 17 [.67] depth	G1/4 14 [.55] depth
M	M27x2 17 [.67] depth	M14x1,5 14 [.55] depth
A	1 1/16 - 12 UN O-ring 17 [.67] depth	7/16 - 20 UNF O-ring 12,7 [.50] depth



	Thread Ports - P _(A,B)	Thread Ports - C
-	G 1 20 [.79] depth	G1/4 14 [.55] depth
M	M33x2 20 [.79] depth	M14x1,5 14 [.55] depth
A	1 5/16 - 12 UN O-ring 20 [.79] depth	7/16 - 20 UNF O-ring 12,7 [.50] depth

Note: KPWT Blocks are installed directly on MT Motors with four screws M10x40 - 8.8 DIN 912.
Tightening torque 3,5 daNm [336 lb-in].

KPWV Blocks are installed directly on MV Motors with four screws M12x45 - 8.8 DIN 912.
Tightening torque 6,5 daNm [425 lb-in].