

Series Industrial ENCLOSED in PAINTED STEEL




S. 440




THE HOSE REELS ARE EQUIPPED WITH A UNIVERSAL HOSE STOP; THOSE WITH HOSE ARE PROVIDED WITH A 0,6 m INLET CONNECTION HOSE.


- The template supplied, facilitates drilling of the holes and therefore hose reel fixing.




- The quick coupling support (see page 82) that facilitates installation in battery is available on request.



- The quick coupling adjustable support (see page 82) that enables 40° rotation to the right or left of the hose reel is available on request.



- The adjustable arms can be easily repositioned according to needs (see page 77).



Air - Water 20 bar

swivel Brass
seals Viton

Article	Capacity l/min Air-Water	Delivery hose	ø Hose	Inlet connection	Outlet connection
Series 440 440/10	800 - 50	without hose	/	F 1/2"G	F 1/2"G
440/11	760 - 47	15m (962/15)	1/2"	F 1/2"G	M 1/2"G
440/12	690 - 30	12m (952/13)	3/8"	F 1/2"G	M 3/8"G
440/13	640 - 25	18m (952/19)	3/8"	F 1/2"G	M 3/8"G
440/14	780 - 48	10m (962/10)	1/2"	F 1/2"G	M 1/2"G

N° 1 packing m³ 0,111 from kg 24 to 29

Oil 150 bar

swivel Steel
seals Polyurethane

Article	Relative capacity	Delivery hose	ø Hose	Inlet connection	Outlet connection
Series 440 440/40	20 l/min	without hose	/	F 1/2"G	F 1/2"G
440/41	14 l/min	10m (963/11)	1/2"	F 1/2"G	M 1/2"G
440/42	12 l/min	15m (963/15)	1/2"	F 1/2"G	M 1/2"G

N° 1 packing m³ 0,111 from kg 24 to 29

Grease 600 bar

swivel Steel
seals Polyurethane

Article	Relative capacity	Delivery hose	ø Hose	Inlet connection	Outlet connection
Series 440 440/50	1200 g/min	without hose	/	F 3/8"G	F 1/2"G
440/51	650 g/min	12m (935/13)	1/4"	F 3/8"G	M 1/4"G
440/52	550 g/min	18m (935/18)	1/4"	F 3/8"G	M 1/4"G
440/55	800 g/min	10m (957/10)	3/8"	F 3/8"G	M 1/4"G
440/56	750 g/min	15m (957/15)	3/8"	F 3/8"G	M 1/4"G

N° 1 packing m³ 0,111 from kg 24 to 29

OVERALL DIMENSIONS

Series	A	B	C	D	E	F	G	H
440	217	140	236	500	485	177	180	236

