



Feuerschutzschlauch - EN45545 / DIN5510-2

Fire protection hose - EN45545 / DIN5510-2

Tuyau de protection contre l'incendie - EN45545 / DIN5510-2

Funda de protección contra incendios - EN45545 / DIN5510-2

Wąż przeciwpożarowy - EN45545 / DIN5510-2

Protezione antifiama per tubi - EN45545 / DIN5510-2

Beschreibung: Silikonbeschichtetes
Fiberglas
Betriebstemperatur: max 260°C kurzfristig
1100°C
Norm: EN45545 und DIN5510-2
UL 1441
Rollenware: <= DN75 20m
> DN75 15m
(kein Anschnitt)

Description: Silicone coated fibreglas
Temperature: max 260°C short time
1100°C
Norm: EN45545 and DIN5510-2
UL 1441
Coil: <= DN75 20m
> DN75 15m
(no short lengths
available)

Part-No.	 mm	 mm	 bar	 mm	 %	 g/m	Price/m
SSCF-6	6	8,4					
SSCF-8	8	10,6					
SSCF-10	10	13,2					
SSCF-12	12	15,4					
SSCF-13	13	16,8					
SSCF-15	15	19,2					
SSCF-20	20	24,6					
SSCF-22	22	27					
SSCF-25	25	30,2					
SSCF-30	30	35,8					
SSCF-32	32	38					
SSCF-35	35	41,2					
SSCF-38	38	44,6					
SSCF-40	40	46,8					
SSCF-45	45	52					
SSCF-50	50	57,4					
SSCF-55	55	62,8					
SSCF-60	60	68					
SSCF-65	65	73,2					
SSCF-70	70	78,6					
SSCF-75	75	83,8					
SSCF-89	89	99					
SSCF-102	102	114					
SSCF-105	105	117					
SSCF-110	110	122					
SSCF-115	115	127					
SSCF-127	127	139					